




LET'S  
**go Haier**  
Inspired living

- AS25TABHRA
- AS50TDBHRA
- AS68TEBHRA
- AS35TACHRA



09/12/18/24K



Remote Control  
(Standard)



Wired Controller  
(Optional)



Wifi Module  
(Optional)



Wi-Fi Control  
(Optional)



On-off Card



### Super quiet

Optimize the noise control technology, such as the compressor frequency adjustment, fan speed control and air flue design decreasing the noise level even lowest to 20dB(A) with the specialized QUIET setting. (refer to 9k)



### Intelligent air

Airflow automatically upward when cooling or downward when heating to spread air automatically throughout the large room while without blowing directly to human body.



### Comfortable sleep

The setting temperature and the indoor noise can be adjusted to a more comfortable level when you set the "sleep mode" during night sleep.



Comfortable  
sleep



-15°C heating



Super quiet



Intelligent air

## WALL TYPE R32 - DC INVERTER

Model	INDOOR	AS25TABHRA	AS35TACHRA	AS50TDBHRA	AS68TEBHRA
	OUTDOOR	1U25BEFFRA	1U35BEEFRA	1U50JEFFRA	1U68REFFRA
Ψυκτική Απόδοση	KW	2,6	3,6	5,2	7
	BTUS/HR	8870(2730-11600)	12280(3410-14330)	17740(4430-23200)	23880(7500-29000)
Θερμαντική Απόδοση	KW	3,4	4,2	6	8,1
	BTUS/HR	11600(3410-15690)	14330(3750-18420)	20470(4770-23540)	27640(8190-34120)
Συντελεστής Απόδοσης (θερμής ζώνης)	SEER/SCOP	6.2/4,9 A++/A++	6.8/4,6 A++/A++	6.8/5,3 A++/A+++	7,1/5,3 A++/A+++
Κατανάλωση (κρύο)	KW	0.80(0.30-1.20)	1.11(0.30-1.60)	1.61(0.40-2.00)	2.16(0.70-2.90)
Κατανάλωση (ζεστό)	KW	0.91(0.30-1.50)	1.13(0.40-1.60)	1.61(0.52-2.35)	2.18(0.70-2.90)
Ρεύμα Λειτουργίας (cooling/heating)	A	max 6.7	max 7.1	max 10.6	max 13
Παροχή Αέρα (υψηλή / μέτρια / χαμηλή)	m <sup>3</sup> /h	500	550	1000	1200
Στάθμη Θορύβου. Εσωτ. Μονάδας (δυναμική/χαμηλή/soft)	Db (A)	35/32/28/20	36/33/29/21	44/40/35/28	47/43/37/30
Στάθμη Θορύβου. Εξωτ. Μονάδας (δυναμική/χαμηλή/soft)	Db (A)	46/47	46/47	51/52	52/53
Διαστάσεις Εσωτ. Μονάδας (ΜxΠxΥ)	mm	820/195/280	820/195/280	1008/225/318	1125/240/335
Διαστάσεις Εξωτ. Μονάδας (ΜxΠxΥ)	mm	780/245/540	780/245/540	820/338/614	890/353/697
Μέγιστη οριζόντια/κάθετη διασώληνωση.	kg	15 - 10 m	15 - 10 m	25 - 15 m	25 - 15 m
Συμπλήρωση αερίου μετά από...../.....g/m	kg	7m/20g/m	7m/20g/m	7m/20g/m	7m/20g/m
Σωλήνες Αερίου	liquid/gas	1/4 - 3/8 "	1/4 - 3/8 "	1/4 - 1/2"	1/4 - 1/2"