Position	Qty.	Description	Single Price
	1	**Unilift KP 250**	Price on request

Note! Product picture may differ from actual product

Product No.: 012H1600
Submersible drainage pump

Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 1-phase canned motor in insulation class F with thermal overload protection.

The pump is fitted with suction strainer and a carrying handle and is supplied with a 3 m mains cable and float switch for automatic start and stop.

The impeller is a semi-open impeller for 10 mm free passage suitable for pumping groundwater, surface water, rain water and similar liquids.

The pump has a double shaft seal consisting of two lip seals with grease in-between.

The pump has an outer casing ensuring continuous cooling of the motor by the pumped liquid.
The rotor shaft operates in two maintenance-free carbon bearings cooled by the pumped liquid.

The motor is filled with a non-toxic motor liquid.

Liquid:

Liquid temperature range:	0 .. 50 °C
Liquid temp:	20 °C
Density:	998.2 kg/m³

Technical:

Resulting head of the pump:	5.49 m
Maximum particle size:	10 mm

Materials:

Pump housing:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
Impeller:	Stainless steel DIN W.-Nr. 1.4031

Position	Qty.	Description		Single Price
			AISI 304	
		Installation:		
		Pump outlet:	Rp 1 1/4	
		Maximum installation depth:	10 m	
		Electrical data:		
		Power input - P1:	480 W	
		Mains frequency:	50 Hz	
		Rated voltage:	1 x 220-230 V	
		Rated current:	2.3 A	
		Capacitor size - run:	8 µF/400 V	
		Enclosure class (IEC 34-5):	68	
		Insulation class (IEC 85):	F	
		Length of cable:	3 m	
		Type of cable plug:	SCHUKO	
		Others:		
		Net weight:	7 kg	
		Gross weight:	6.7 kg	
		Shipping volume:	0.013 m3	

012H1600 Unilift KP 250 A 1 50 Hz





012H1600 Unilift KP 250 A 1 50 Hz





Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.